

Alpha D01C2M1

alpha series™

- 4 Channel DVR, 4 Indoor/Outdoor Cameras & 7" LCD Monitor



Never lose the remote control again!
Easily detach to use as a remote or front control panel

- Complete 4 camera surveillance with crystal clear LCD monitor for peace of mind at an affordable price, with no ongoing costs
 - Easily backup & retain video evidence if there's an incident
 - Set & forget by recording continuously from 4 cameras for over 60 days+
 - Catch suspicious activity & save hard drive space with motion detection
 - Protect the people you care about & reduce the cost of crime
- + Depending on recording settings

Features ▶

4
Channels view & record

320
GB 2 months continuous recording*

USB easily backup video incidents to flash drive

400 high video quality
1/3" CMOS 400 TV lines

30ft 9m
good night vision

weather resistant cameras
anti-corrosive casing

BNC cable x 4
50ft 15m

front

back



Product Code ▶

SWA44-D1C2M1

Swann

| Swann Alpha Range 2010 ▶

Alpha D01C2M1

- 4 Channel DVR,
4 Indoor/Outdoor Cameras
& 7" LCD Monitor

Specifications ▶

DVR

Video

Video Format	NTSC or PAL
Video Inputs	4CH Composite
Video Outputs	1CH Composite
Display Resolution	NTSC: 640 x 448 / PAL: 640 x 544
Display Frame Rate	NTSC: 120fps (4 x 30) / PAL: 100fps (4 x 25)

Audio

Audio Input	1 RCA Input
Audio Output	1 RCA Output

Recording

Compression Format	Advanced MJPEG
Recording Resolution	NTSC: 640 x 224 / PAL: 640 x 272
Recording Frame Rate	NTSC: 60fps Quad View / PAL: 50fps Quad View
Recording Modes	Manual / Schedule / Motion
Multiplex Operation	Triplex
HDD Interface / Memory Type	SATA
Hard Drive Support	Up to 1TB

General

Operating Power	DC 12V
Dimensions	8.9" x 8.2" x 2.1" / 225mm x 208mm x 53mm
Weight	2.8lbs / 1.3kg
Backup Method	USB to Flash Drive
Remote Control	Yes, 2 in pack
Remote Control Battery Type	Lithium battery CR2025 / 3V

Camera

Video

Image Sensor	1/3" CMOS
Video Quality	400 TV Lines
Number of Effective Pixels	NTSC: 510 x 492 / PAL: 628 x 582
Minimum Illumination	0 Lux (IR on)
Day/Night Mode	Color during day / switches to B&W at night

White Balance	Automatic
Signal / Noise Ratio	> 50dB
Electronic Shutter	1/60 - 1/15,000 NTSC / 1/50 - 1/15,000 PAL

Gain Control	Automatic
Backlight Compensation	Yes
Wide Dynamic Range	No
Lens	6mm
Viewing Angle	53 degrees



Pack Contents ▶

- Alpha D01 DVR
- 320GB Hard Drive (installed)
- Alpha C2 Cameras x 4
- 7" LCD Monitor & Accessories
- RCA to RCA Cable 6ft / 2m
- BNC Cables 50ft / 15m x 4
- BNC to RCA Adapters
- Power Adapters
- Remote Control x 2
- Mounting Screws & Plugs
- Operating Instructions
- Theft Deterrent Stickers x 4

Audio

Microphone	No
------------	----

Night Vision

Night Vision Distance	Up to 30ft / 9m
IR Cut Filter	No
Number of Infra-Red LEDs	30
Infra-Red Wavelength	850nm
Infra-Red LED Life	10,000 hours

General

Indoor / Outdoor	Indoor / Outdoor
Operating Power	DC 12V
Operating Temperature	14°F ~ 122°F / -10°C ~ 50°C
Body Construction	ABS Plastic
Dimensions - Camera	5.5" x 2.8" x 2.8" / 140mm x 70mm x 70mm
Dimensions - Stand	4.5" x 2.3" x 2.3" / 120mm x 60mm x 60mm
Weight - Camera	0.4lbs / 180g
Weight - Camera & Stand	0.5lbs / 235g
Cable Length	50ft / 15m

LCD Monitor

Display

Screen Size	7 inches
Screen	TFT
LCD Profile Ratio	Ratio 16 : 9
Display Resolution	1440 (H) x 234 (V)
Contrast	300 : 1
Brightness	300cd / m2
Response Time (ms)	R 15 / F: 20
Viewing Angle	U: 40 / D: 60 L/R: 60
Video Input	1VP-P 75 Ohm

Audio

Audio Input	1.5VP-P Stereo (left and right)
Audio Output	Build-in louder speaker (0.3w * 2)

General

Power Supply	DC 12V
Connecting Terminal	AV input jack x 2 external power supply jack
Languages	English, Russian, German, French, Spanish, Portugese, Italian and Dutch changeable OSD menu
Remote Control	Yes
Battery QTY & Type	2 x AAA
Operation Temperature	14°F ~ 122°F / -10°C ~ 50°C
Power Consumption	Approx. 10W

Packaging

Pack Weight	19.8lbs / 9kg
Pack Dimensions (HxWxD)	13.8" x 19.7" x 7.9" / 350mm x 500mm x 200mm
Master Pack Quantity	2
Master Pack Dimensions (HxWxD)	14.2" x 17.1" x 25.8" / 360mm x 435mm x 655mm

