

IP-3G ConnectCam 1000™



Day & Night Wireless 802.11G Network Camera

View live video from anywhere in the world over the web



- See, hear & talk via PC, Laptop or 3G mobile phone
- See your home or business from the other side of the globe!
- Capture images & have them emailed instantly to mailbox
- Doesn't need to connect to PC to establish network connection*
- Wireless 802.11G technology
- MPEG4 & MJPEG compression for increased storage capacity

USB port for
memory stick dump



IP-3G Connect Cam 1000™

Day & Night Wireless 802.11G Network Camera

View live video from anywhere in the world over the web



View your cameras over the internet!

The IP-3G ConnectCam 1000™ network camera is designed to work with your existing wired or wireless network and is compatible with standard 802.11b/g wireless devices including compatible 3G cell phones. With the flexibility to operate the camera without a network cable the ConnectCam 1000 can be placed anywhere within your wireless network range. Utilizing SSID filtering and powerful 64/128 bit WEP encryption, the ConnectCam 1000 helps to protect your wireless network camera from illegal intrusion. Watch your kids at home from the office or monitor your home while on vacation with peace of mind thanks to the ConnectCam 1000 network camera.



2-Way Audio and Motion Detection Alerts!

Once the initial setup is complete, place your cameras anywhere you need them to view and speak anywhere in the world. With 2-way voice capabilities you can speak with whoever is in the camera range making it ideal for job sites, conference calls or keeping an eye on the kids. The ConnectCam 1000 can also be set to email motion alerts to your inbox when movement is detected. Feature packed and easy to setup, the IP-3G ConnectCam 1000™ offers wireless video anywhere in the world.



IP-3G Connect Cam 1000™

Day & Night Wireless 802.11G Network Camera

View live video from anywhere in the world over the web



The IP-3G ConnectCam 1000™ can be either wall-mounted or ceiling-mounted with the fixture plate or placed on a desktop using the supplied camera stand, providing flexible installation to meet your specific needs. The IP-3G ConnectCam 1000™ has built-in motion detection and can detect when the picture being monitored changes. Once movement occurs, the camera will capture the picture and email it to your designated email address (maximum 3) and FTP server. When you receive a message you can log into your camera or take necessary action. The ConnectCam 1000 has a built-in microphone and audio output for speaker connections allowing the viewer to communicate with anyone within the camera's range.



With the software iNetwork Camera Viewer you can get images from 16 cameras* at the same time.

* Depends on computer specifications and software installed. Wireless broadband modem required for wireless connection.

^ We recommend cable/DSL internet connection access be used.

Applications:



See & hear loved ones



Stay in touch on the road



Protect your property



IP-3G Connect Cam 1000™

Day & Night Wireless

802.11G Network Camera

View live video from anywhere in the world over the web



Product Specifications

Image Sensor

Sensor	¼" Color CMOS Sensor
Resolution	640 x 480 Pixel
Lens	f: 4.6mm, F 2.8 (IR Lens)
Viewing Angle	60 Degree
Minimum Illumination	0.5Lux @ F2.0

Audio

Microphone Input	Internal Omni-Directional
Audio Output	3.5mm Speaker Output Jack
Format	PCM/AMR (Mono)

Video/Image Setting

Video Format	MPEG4 (Simple Profile), MJPEG, 3GPP
Image Frame Rate	30fps @ VGA, QVGA, QQVGA
Frame Rate Setting	1 ~ 30fps
Resolution	640 x 480, 320 x 240, 160 x 120
Flip Images	Vertical / Horizontal
Light Frequency	50Hz, 60Hz or Outdoor

Communication

LAN	10/100Mbps Auto MDIX
Protocol	HTTP, FTP, TCP/IP, UDP, ICMP, DHCP, NTP, DNS, DDNS, SMTP, PPPoE, UPnP, RTP, RTSP, RTCP

System Requirements (Web Configuration)

CPU	Pentium III 350MHz or above
Memory Size	128MB or above
Resolution	800 x 600 or above
Browser	Internet Explorer 6.0 or above
Supported OS	Windows 2000/XP/Vista

System Requirement (SecuraView™ Software)

CPU	Pentium 4 1GHz or above
Memory Size	512MB or above
Resolution	1024 x 768 or above
Supported OS	Windows 2000/XP/Vista

Physical / Environment

Dimension	70mm x 100mm x 57mm (2.67" x 3.94" x 2.95")
Weight	Camera 170g (6 oz.) Stand 135g (4.76 oz.)
Power	5VDC, 2.5A External Power Adapter
Power Consumption	8 Watts (Max)
Temperature	Operation: 0° ~ 45°C (32°F ~ 113°F) Storage: -10°C ~ 60° (14°F ~ 140°F)
Standard	IEEE 802.11b/g
Security	64/128-bit WEP WPA-PSK, WPA2-PSK

Other

USB Port	USB 1.1 (Type 1) Up to 500mA Power Device with FAT16/32 Format
----------	---

Package Contents

- IP-3G ConnectCam 1000™ Network Camera
- External Antenna
- AC Power Adapter
- Camera Stand
- Ethernet Cable
- Installation CD Software
- Instruction Manual
- 4 x Warning Stickers